

# KERN PCB 200-2

The standard in the laboratory

# KERN®



## Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	30 mg
Linearity:	20 mg
Readability [d]:	10 mg
Recommended adjusting weight:	200 g (M1)
Repeatability:	10 mg
Resolution:	20000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	30 min
Weighing capacity [Max]:	200 g
Weighing system:	Strain gauge
Weighing units:	kg lb ozt gn ct dwt mo oz tl (Tw) tl (HK) tol g

## Display

Display digit height (large):	1,500 cm
-------------------------------	----------

## Counting

Counting resolution:	10000
Minimum piece weight at piece counting (Laboratory):	20 mg
Minimum piece weight at piece counting (Normal):	200 mg

## Functions

Counting function:	yes
Percentage determination:	yes
Suspended weighing:	Hook
Vibration-free weighing (Animal weighing program):	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

## Power supply

Battery:	9 V Block
Charging time:	8 h
Input voltage:	100-240V AC 50/60Hz 0.5A
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH US UK
Operating time:	20 h
Operating time (Backlight off):	48 h
Operating time (Backlight on):	24 h
Rechargeable battery:	Rchrg. battery optional

## Services (optional)

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

## Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	230 x 360 x 180 mm
Gross weight:	1,540 kg
Net weight:	1,020 kg
Shipping method:	Parcel service

## Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	163 x 245 x 79 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Weighing surface (d):	105

# KERN PCB 200-2

The standard in the laboratory



## Piktogramme

### STANDARD



### OPTION

